



## FEATURES

- Multi-Function Display.
- True 10 bits Color processing engine
- Wide viewing angle.
- Wall mountable capability
- Capacitive touch monitor.
- Panel Mount
- Protectable Metal Housing

| IM-10001          |                                                                                             |
|-------------------|---------------------------------------------------------------------------------------------|
| LCD PANEL         | 15”                                                                                         |
| ACTIVE AREA       | 378 x 297 (MM)                                                                              |
| PICTURE FORMAT    | 4:3                                                                                         |
| RESOLUTION        | 1024 X 768                                                                                  |
| IP RATING         | IP65                                                                                        |
| COLORS            | 16.7                                                                                        |
| BRIGHTNESS        | 400 cd/m²[LED]                                                                              |
| CONTRAST RATIO    | 700:1                                                                                       |
| RESPONSE TIME     | 7/5 MS(Tr/Tf)                                                                               |
| VIEW ANGLE        | 80/80/70/80                                                                                 |
| TOUCH TYPE        | Capactive touch                                                                             |
| USB               | 1x USB For Touch                                                                            |
| DISPLAY OUT       | 1xVGA ,1 HDMI                                                                               |
| DVI               | Optional                                                                                    |
| OSD               | Yes                                                                                         |
| POWER SUPPLY      | AC 100 – 240 V                                                                              |
| POWER CONSUMPTION | < 30W                                                                                       |
| WORKING VOLTAGE   | 12V                                                                                         |
| OPERATING TEMP    | -10°C to 60° C                                                                              |
| POWER INPUT       | AC 100-240V 50/60Hz, Adapter DC 12V/5A                                                      |
| WARRANTY          | 1 YEAR                                                                                      |
| ACCESSORIES       | 1 * Power Adaptor,1* VGA Cable, 1* HDMI Cable, 1 * Panel Mount Clamp<br>1* USB Touch Cable. |