



FEATURES

- 13.3" true color LCD display with 1920\*1080 resolution
- The front panel is IP65 rated to prevent dust and splashing water droplets from entering the display.
- Intel i5-4<sup>th</sup> Gen Processor.
- 9 ~ 36V wide voltage DC power input.
- High-precision capacitive screen
- Both panel embedded and standard VESA mounting are supported.
- 4 x USB, 2 x GLAN

| PPC-02001                  |                                                                                               |
|----------------------------|-----------------------------------------------------------------------------------------------|
| SIZE                       | 13.3”                                                                                         |
| CPU                        | I5-4260U Processor 1.40Ghz With 15W TDP                                                       |
| RAM                        | 1*DDR3L SODIMM memory slot support single channel 1600/1333MHz<br>DDR3L/1.35V memory, max 8GB |
| RESOLUTION                 | 1920 * 1080                                                                                   |
| STORAGE                    | 1 * M-SATA, 1 * SATA                                                                          |
| ETHERNET                   | 2 * RJ45                                                                                      |
| AUDIO                      | RTLALC662 audio controller, LINE-out port                                                     |
| USB                        | 3 *USB 3.0 Port 1 *USB 2.0 Port                                                               |
| SERIAL PORT                | 3 x RS232 COM or 6 x RS232 COM + 2 x RS485/RS422 COM                                          |
| BRIGHTNESS                 | 250Cd/m2                                                                                      |
| GPIO                       | 14 BIT                                                                                        |
| DISPLAY                    | 13.3” TFT LED                                                                                 |
| CONTRAST                   | 800:1                                                                                         |
| MAXIMUM COLOR              | 16M                                                                                           |
| TOUCH                      | High precision capacitive                                                                     |
| CLICK LIFE CYCLE           | 250 grams of strength, 50 million times                                                       |
| RESPONSE TIME              | <5ms                                                                                          |
| TRANSMITTANCE              | above 91%                                                                                     |
| HIGH TEMPERATURE           | 85°C/1000hr                                                                                   |
| CONSTANT TEMP AND HUNIDITY | 85°C/90%RH/1000hrs                                                                            |
| INSTALLATION               | VESA mountable with bracket                                                                   |
| POWER INPUT                | 9~36V DC power supply                                                                         |
| DIMENSION                  | 338mm x 215mm x 43mm                                                                          |
| CABINET                    | Aluminium profile face frame Abrasive back shell                                              |
| POWER CONSUMPTION          | 30W                                                                                           |
| FRONT PANEL                | IP65 STANDARD                                                                                 |
| OPERATING TEMPERATURE      | -20~60°C                                                                                      |
| STORAGE TEMPERATURE        | -30~80°C                                                                                      |
| WARRANTY                   | 2 Years                                                                                       |