



FEATURES

- 10.4" true color LCD display with 1024*768 resolution
- The front panel is IP65 rated to prevent dust and splashing water droplets from entering the display.
- Intel i5-7th Gen Processor.
- 9 ~ 36V wide voltage DC power input.
- High-precision capacitive screen
- Both panel embedded and standard VESA mounting are supported.
- 4 x USB, 2 x GLAN

PPC-02002	
SIZE	10.4”
CPU	I5-7200U
RAM	4GB DDR3/4 onboard (extensible)
RESOLUTION	1024 * 768
STORAGE	1 * M-SATA,
ETHERNET	2 * RJ45
AUDIO	RTLALC662 audio controller, LINE-out port
USB	4 *USB 3.0 Port
SERIAL PORT	4 x RS232+1 x RS485+1 x (RS232/422/485)optional
BRIGHTNESS	250cd/m2
DISPLAY	10.4” TFT LED
CONTRAST	800:1
MAXIMUM COLOR	16M
TOUCH	High precision capacitive
CLICK LIFE CYCLE	250 grams of strength, 50 million times
RESPONSE TIME	<5ms
TRANSMITTANCE	above 90%
HIGH TEMPERATURE	85°C/1000hr
CONSTANT TEMP AND HUNIDITY	85°C/90%RH/1000hrs
INSTALLATION	VESA mountable with bracket
POWER INPUT	9~36V DC power supply
DIMENSION	288mmx230mmx51mm
CABINET	Aluminium profile face frame Abrasive back shell
POWER CONSUMPTION	30W
FRONT PANEL	IP65 STANDARD
OPERATING TEMPERATURE	-20~60°C
STORAGE TEMPERATURE	-30~80°C
WARRANTY	2 years