



FEATURES

- 10.1" true color LCD display with 1024*768 resolution
- The front panel is IP65 rated to prevent dust and splashing water droplets from entering the display.
- Intel i5-4th Gen Processor.
- 9 ~ 36V wide voltage DC power input.
- High-precision capacitive screen
- Both panel embedded and standard VESA mounting are supported.
- 4 x USB, 2 x GLAN

PPC-02003	
SIZE	10.1”
CPU	I5-4200U
RAM	1* DDR3 SODIMM Max 8GB
RESOLUTION	1280 * 800
STORAGE	1 * M-SATA,
ETHERNET	2 * RJ45
AUDIO	RTLALC662 audio controller, LINE-out port
USB	2 *USB 3.0 Port , 2*USB 2.0 Port.
SERIAL PORT	6 x RS232/2 (422/485)
BRIGHTNESS	250cd/m2
DISPLAY	10.1” TFT LED
CONTRAST	800:1
MAXIMUM COLOR	16M
TOUCH	High precision capacitive
CLICK LIFE CYCLE	250 grams of strength, 50 million times
RESPONSE TIME	<5ms
TRANSMITTANCE	above 95%
HIGH TEMPERATURE	85°C/1000hr
CONSTANT TEMP AND HUNIDITY	85°C/90%RH/1000hrs
INSTALLATION	VESA mountable with bracket
POWER INPUT	9~36V DC power supply
DIMENSION	261.6mm x 161mm x 48mm
CABINET	Aluminium profile face frame Abrasive back shell
POWER CONSUMPTION	30W
FRONT PANEL	IP65 STANDARD
OPERATING TEMPERATURE	-20~60°C
STORAGE TEMPERATURE	-30~80°C
WARRANTY	2 years