



FEATURES

- 10.1" true color LCD display with 1280*800 resolution
- The front panel is IP65 rated to prevent dust and splashing water droplets from entering the display.
- Intel Celeron Processor.
- 12V DC power input.
- High-precision capacitive screen
- Both panel embedded and standard VESA mounting are supported.
- 2x USB, 2 x GLAN

PPC-02004	
SIZE	10.1”
CPU	J1900
RAM	1* DDR3 1600/1333Mhz SODIMM Max 8GB
RESOLUTION	1280 * 800
STORAGE	1 * mSATA, 1 * SATA 2.5, 1 * SATA 2.0 Pin
ETHERNET	2 * RJ45
AUDIO	1 x MIC; 1 x Line-out
USB	1 *USB 3.0 Port , 1*USB 2.0 Port.
BRIGHTNESS	350 350cd/m2
DISPLAY	10.1” TFT LED
CONTRAST	800:1
MAXIMUM COLOR	16M
TOUCH	High precision capacitive
CLICK LIFE CYCLE	120 grams of strength, 50 million times
RESPONSE TIME	<5ms
TRANSMITTANCE	above 85%
HIGH TEMPERATURE	85°C/1000hr
CONSTANT TEMP AND HUNIDITY	85°C/90%RH/1000hrs
INSTALLATION	VESA mountable with bracket
POWER INPUT	12V DC power supply
DIMENSION	253mm x 171.6mm x 41.5mm
CABINET	Aluminium profile face frame Abrasive back shell
POWER CONSUMPTION	30W
FRONT PANEL	IP65 STANDARD
OPERATING TEMPERATURE	-20~60°C
STORAGE TEMPERATURE	-30~80°C
WARRANTY	2 years