



FEATURES

- Multi-Function Display
- True 10 bits color processing engine
- Wide viewing angle
- Wall mountable capability
- Capacitive touch monitor
- Panel Mount
- Protectable Metal Housing

IM-10016	
LCD PANEL	18.5"
ACTIVE AREA(MM)	482 x 302
PICTURE FORMAT	16: 9
MAX. RESOLUTION	1920 x 1080
IP RATINGS	IP65
COLOURS	16.7M
BRIGHTNESS	1000 cd/m ²
CONTRAST	800 :1
RESPONSE TIME (TR/TF)	7/5 MS
VIEW ANGLE (U/D/L/R)	80°/80°/75°/75° (R/L/U/D)
TOUCH	Capacitive touch
USB	1x USB For Touch
DISPLAY OUT	1xVGA ,1 HDMI
DVI	Optional
OSD	Yes
POWER SUPPLY	AC 100 – 240 V
POWER CONSUMPTION	< 30W
WORKING VOLTAGE	12v
OPERATING TEMPERATURE	-20°C to 70° C
POWER INPUT	AC 100-240V 50/60Hz, Adapter DC 12V/5A
ACCESSORIES	1 * Power Adaptor,1* VGA Cable, 1* HDMI Cable, 1 * Panel Mount Clamp, 1* USB Touch Cable
WARRANTY	1 Year