



FEATURES

- 17" true color LCD, resolution 1280 x 1024 backlight service life up to 30000 hours.
- 9v ~ 36v voltage DC power input, to meet the industrial field power supply.
- The ultra-thin design saves cabinet space and is resistant to shock and vibration.
- And it has many industrial site application features, while supporting panel embedded and standard VESA installation, users can flexibly choose the installation method.

PPC-01002	
LED DISPLAY	17"
CPU	Intel Core i5-8260U Processor 4Core 8 thread processor, TDP 15W
RAM	Support 2 x DDR4 SO-DIMM 2400MHz MAX 32GB
MAX. RESOLUTION	1280 x 1024
STORAGE	1 x M-SATA/ 1* SATA, 1*M.2 SSD port, support Key-M, 2280, NVME PCIe4 SSD
NETWORK PORT	2*Intel I210 Gigabit Ethernet, support Wake On LAN、PXE
AUDIO	1* Line out port,1* MIC port
USB	2* USB2.0 port, 4* USB3.0 port
BRIGHTNESS	250cd/m2
COM PORT	6*RS232, COM1 DB9, COM2 DB9 RS232/485/422, COM3-6 RS232/485 on 2*10pin Phoenix connector, COM1-2 support pin9 charged function
TOUCH	Capacitive, 10points
DISPLAY PORTS	1x HDMI
CONTRAST	1000:1
PHOENIX CONTACT	2*10PIN (4-in 4out GPIO, switch signal, COM3~COM6 (RS232/RS485), 24V VCC, GND)
OS SUPPORT	Windows / Linux
INSTALLATION METHOD	Embedded, with support for VESA installation, Desktop, Wall-Mounted
POWER INPUT	12V ~ 36V DC power supply
DIMENSION	L396*W333*H64mm
IP RATINGS	IP65
OPERATING TEMPERATURE	-10℃~50℃
STORAGE TEMPERATURE	-20℃~70℃
CERTIFICATION	CE, FCC, RoHS
WARRANTY	1 Year