

## **FEATURES**

- 15" true colour LED, resolution 1024X768 optional, backlight service life up to 30000 hours.
- The touch screen uses a full plane capacitive touch screen, up to 1 million clicks.
- 12v voltage DC power input, to meet the industrial field power supply.
- The ultra-thin design saves cabinet space and is resistant to shock and vibration.
- High-precision capacitive touch screen, with many industrial site application features, while supporting panel embedded and standard VESA installation, users can flexibly choose the installation method.

PPC-02006	
LED DISPLAY	-
CPU	Intel Core i7-8569U Quad core Eight Thread processor with 28W TDP
RAM	Support DDR4 SO-DIMM 2400MHz MAX 64GB
MAX.	1024 x 768
RESOLUTION	4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
STORAGE	1 x mini-SATA,1 x 2.5-inch HDD/SSD bay
NETWORK PORT	2 x Realtek RTL8111H/8111G 1000M ETH
AUDIO	1 x Line-out/MIC IN
USB	6* USB 3.0 port & 2* USB 2.0
BRIGHTNESS	300cd/m2
COM PORT	6 x COM optional (COM 1 support 485, COM 2 support RS422)
MAXIMUM	16M
COLOR	
DISPLAY PORTS	1 x VGA, 1x HDMI, 1 x LVDS
CONTRAST	800:1
TYPES	10 Point projected capacitive
CLICK LIFE	>1 million times
RESPONSE TIME	<10ms
GPIO	1 x 8 channel GPIO
HIGH	85°C/1000hrs
TEMPERATURE	
TEST	
OS SUPPORT	Windows / Linux
INSTALLATION	Embedded, with support for VESA installation, Desktop, Wall-Mounted
METHOD	
POWER INPUT	12 DC power supply
DISPLAY	378mm x 297mm x 68.8mm
DIMENSION	
IP RATINGS	IP65
OPERATING	-20°C∼60°C
TEMPERATURE	
STORAGE	-30°C∼80°C
TEMPERATURE	
CERTIFICATIONS	CE, FCC
WARRANTY	2 Years