



FEATURES

- 23.8" true color LED, resolution 1920X1080 backlight service life up to 30000 hours.
- 12v ~ 36v voltage DC power input, to meet the industrial field power supply.
- The ultra-thin design saves cabinet space and is resistant to shock and vibration.
- And it has many industrial site application features, while supporting panel embedded and standard VESA installation, users can flexibly choose the installation method.

| PPC-02008             |                                                                     |
|-----------------------|---------------------------------------------------------------------|
| LED DISPLAY           | 23.8"                                                               |
| CPU                   | Intel Core i5-8250U Processor 4Core 8 thread processor, TDP 15W     |
| RAM                   | Support DDR4 SO-DIMM 2400MHz MAX 32GB                               |
| MAX. RESOLUTION       | 1920 x 1080                                                         |
| STORAGE               | 1 x M-SATA/ 1* SATA                                                 |
| NETWORK PORT          | 2 * Rj45 Realtek Chipset                                            |
| AUDIO                 | 1 x Line-out/MIC IN                                                 |
| USB                   | 4* USB 3.0                                                          |
| BRIGHTNESS            | 350cd/m2                                                            |
| COM PORT              | 2 x RS232                                                           |
| MAXIMUM COLOR         | 16M                                                                 |
| DISPLAY PORTS         | 1 x VGA, 1x HDMI                                                    |
| CONTRAST              | 1000:1                                                              |
| HIGH TEMPERATURE TEST | 85°C/1000hrs                                                        |
| OS SUPPORT            | Windows / Linux                                                     |
| INSTALLATION METHOD   | Embedded, with support for VESA installation, Desktop, Wall-Mounted |
| POWER INPUT           | 12V ~ 36V DC power supply                                           |
| DISPLAY DIMENSION     | 584mm x 355.5mm x 59mm                                              |
| IP RATINGS            | IP65                                                                |
| OPERATING TEMPERATURE | -20°C~60°C                                                          |
| STORAGE TEMPERATURE   | -30°C~80°C                                                          |
| CERTIFICATIONS        | CE, FCC                                                             |
| WARRANTY              | 1 Year                                                              |