



FEATURES

- 15" true color LED, resolution 1024X768 backlight service life up to 30000 hours.
- 9v ~ 36v voltage DC power input, to meet the industrial field power supply.
- The ultra-thin design saves cabinet space and is resistant to shock and vibration.
- And it has many industrial site application features, while supporting panel embedded and standard VESA installation, users can flexibly choose the installation method.

PPC-02009	
LED DISPLAY	15"
CPU	Intel Core i5-7200U Processor 2Core 4 thread processor, TDP 15W
RAM	Support DDR3 SO-DIMM 2400MHz
MAX. RESOLUTION	1024 x 768
STORAGE	1 x M-SATA/ 1* SATA
NETWORK PORT	2 * Rj45
AUDIO	1 x Line-out/MIC IN
USB	4* USB 3.0
BRIGHTNESS	350cd/m2
COM PORT	6x RS232/2 x (422/485)
MAXIMUM COLOR	16M
DISPLAY PORTS	1x HDMI
CONTRAST	800:1
TOUCH	Capacitive
OS SUPPORT	Windows / Linux
INSTALLATION METHOD	Embedded, with support for VESA installation, Desktop, Wall-Mounted
POWER INPUT	9V ~ 36V DC power supply
DISPLAY DIMENSION	370mm x 290mm x 48mm
IP RATINGS	IP65
OPERATING TEMPERATURE	-20°C~60°C
STORAGE TEMPERATURE	-30°C~80°C
CERTIFICATIONS	CE, FCC
WARRANTY	1 Year