



FEATURES

- 12.1" true color LED display with 1280*800 resolution and a backlight service life of up to 50000 Hours.
- The front panel is IP65 rated to prevent dust and splashing water droplets from entering the display.
- Ultra-thin design, save cabinet space, shock, and vibration resistance.
- 12 ~ 36V wide voltage DC power input, meet the industrial field power supply.
- High-precision capacitive screen, with many application characteristics in industrial sites.
- Both panels embedded and standard VESA mounting are supported, allowing users to flexibly choose the installation method.

PPC-02011	
LCD DISPLAY	12.1"
CPU	i5-7200U
RAM	2*DDR4 SODIMM memory slot max 32GB
MAX. RESOLUTION	1280x800
STORAGE	1* M.2 SATA
NETWORK PORT	2 x Intel Gigabit Ethernet
AUDIO	RTLALC662 audio controller, LINE-out port
USB	2 * USB 3.0 port, 2 * USB 2.0
SERIAL PORT	2 x RS232 COM
BRIGHTNESS	350cd/m2
DISPLAY	12.1" TFT LED
CONTRAST	1200:1
MAXIMUM COLOR	16M
TYPES	High precision capacitive
CLICK LIFE	250 grams of strength, 50 million times
RESPONSE TIME	< 5ms
TRANSMITTANCE	above 85%
HIGH TEMPERATURE TEST	85°C/1000hr
CONSTANT TEMPERATURE AND HUMIDITY TEST	85°C/90%RH/1000hrs
INSTALLATION METHOD	Embedded in panel, VESA mountable with bracket
POWER INPUT	12V DC power supply
OVERALL DIMENSION	317mm x 258mm x 67mm
PANEL CABINET	Aluminium profile face frame Abrasive back shell
OPERATING TEMPERATURE	0~50°C
STORAGE TEMPERATURE	-20~80°C
CERTIFICATIONS	CE, FCC
WARRANTY	1 Year