



FEATURES

- 21.5" true color LCD, resolution 1920 x 1080.
- The touch screen uses a full plane capacitive touch screen, up to 35 million clicks.
- 2pin Phoenix Power connector to meet the industrial field power supply.
- The ultra-thin design saves cabinet space and is resistant to shock and vibration.
- High-precision capacitive touch screen, with many industrial site application features, while supporting panel embedded and standard VESA installation, users can flexibly choose the installation method.

PPC-10003	
LCD DISPLAY	21.5”
CPU	Intel Core i3 -7th Gen CPU
RAM	2 * DDR4 2133/2400/1866MHz Memory slots, up to 32GB
MAX. RESOLUTION	1920 x 1080
STORAGE	1* SATA3.0 1* M.2 KeyM Slot, supporting SSD
NETWORK PORT	2* Realtek RTL8111H Gigabit network card, supporting wake-on-LAN/PXE
AUDIO	1 x MIC; 1 x Line-out, 2* 5W speaker
USB	USB 3.0x2, USB2.0X3
BRIGHTNESS	350cd/m2
EXPANSION	1* Mini-PCIe Slot, supporting WIFI/4G 1* PCIE3.0 X4 Slot
GRAPHICS	CPU Integrated graphics HD Graphics and support 1080p HD photo quality
CONTRAST	1000:1
DISPLAY RATIO	16:9
TYPES	10point projective capacitive
VIEW ANGLE	85°/85°/85°/85° (R/L/U/D)
RESPONSE TIME	15ms
DISPLAY PORTS	1 * VGA, 1 * HDMI (support 4K display)
SERIAL PORTS	6 * RS232
CONSTANT TEMPERATURE AND HUMIDITY TEST	5%~95% @ 40° C, non-condensing
INSTALLATION METHOD	wall-mounting, VESA 100×100mm
POWER INPUT	Support 12~19V DC power supply
OVERALL DIMENSION	552mm x339mm x57mm
OPERATING TEMPERATURE	-10℃~60℃
STORAGE TEMPERATURE	-20℃~70℃
CERTIFICATION	CE, FCC, RoHS
WARRANTY	1 Year