## PPC-10004



## **FEATURES**

- 7" true color LCD, resolution 1024 x 600.
- The touch screen uses a full plane capacitive touch screen, up to
  35 million clicks.5 Wires Resistive touch solution.
- 12v DC in supply.
- The ultra-thin design saves cabinet space and is resistant to shock and vibration.
- High-precision capacitive touch screen, with many industrial site application features, while supporting panel embedded and standard VESA installation, users can flexibly choose the installation method.

PPC-1004	
LCD DISPLAY	7"
CPU	Intel® Celeron J1900 (Fanless), Core i3/ i5 / i7
RAM	1 * DDR3 2133Mhz Memory slots, up to 8GB
MAX.	1024 x 600
RESOLUTION	
STORAGE	1* SATA3.0 & 1* M-SATA, supporting SSD
NETWORK PORT	1×Realtek RTL 8111E Gigabit Ethernet controller
AUDIO	Realtek ALC662, High-Definition Audio
USB	USB 3.0x2, USB2.0X2
BRIGHTNESS	350cd/m2
EXPANSION	2* Mini-PCIE expansion slot, support WIFI/3G/4G/MSTA/GPS/Bluetooth
GRAPHICS	CPU Integrated graphics HD Graphics and support 1080p HD photo quality
CONTRAST	500:1
DISPLAY RATIO	16:9
TYPES	10point projective capacitive
VIEW ANGLE	85°/85°/85° (R/L/U/D)
RESPONSE TIME	15ms
DISPLAY PORTS	1 * VGA, 1 * HDMI (support 4K display)
SERIAL PORTS	2 * RS232
CONSTANT	5%~95% @ 40° C, non-condensing
TEMPERATURE	
HUMIDITY TEST	Non-condensing
INSTALLATION	wall-mounting, VESA 100×100mm
METHOD	
POWER INPUT	Support 12v DC power supply
OVERALL	196mm x140.8mm x48.2mm
DIMENSION	or reconour
CERTIFICATION	CE, FCC, ROHS
OPERATING	-10°C∼60°C
TEMPERATURE STORAGE	2000 - 7000
TEMPERATURE	-20°C∼70°C
WARRANTY	1 Year
WAINIANTI	I I Cai