

## **FEATURES**

- 15" true colour LCD, resolution 1024 x 768.
- The touch screen uses a full plane capacitive touch screen, up to
  35 million clicks.
- 12v DC in supply.
- The ultra-thin design saves cabinet space and is resistant to shock and vibration.
- High-precision capacitive touch screen, with many industrial site application features, while supporting panel embedded and standard VESA installation, users can flexibly choose the installation method.

PPC-10006	
LCD DISPLAY	15"
CPU	Inter Celeron J1900, quad core, 2.0Ghz, fanless
RAM	1 * DDR3 1333Mhz Memory slots, up to 8GB
MAX.	1024X768
RESOLUTION	
STORAGE	1* SATA3.0 & 1* M-SATA, supporting SSD
NETWORK PORT	2×Realtek RTL 8111E10M/100M/1000M,
AUDIO	Realtek ALC662, High-Definition Audio
USB	USB3.0(External 2 * USB3.0) USB2.0(External 2 * USB2.0)
BRIGHTNESS	250cd/m2
EXPANSION	2* Mini-PCIE expansion slot, support WIFI/3G/4G/MSTA/GPS/Bluetooth
GRAPHICS	CPU Integrated graphics HD Graphics and support 1080p HD photo quality
CONTRAST	800:1
DISPLAY RATIO	4:3
TYPES	10 point projective capacitive
VIEW ANGLE	85°/85°/85° (R/L/U/D)
RESPONSE TIME	<8ms
DISPLAY PORTS	1 * VGA, 1 * HDMI
SERIAL PORTS	2 * RS232
CONSTANT	5%~95% @ 40° C, non-condensing
TEMPERATURE	
AND HUMIDITY	
TEST	W
INSTALLATION	wall-mounting, VESA 100×100mm
METHOD	Compared 12 o DC managements
POWER INPUT	- Support 12v DC power supply
OVERALL DIMENSION	378mm x297mm x57mm
CERTIFICATION	CE, FCC, FOHS
OPERATING	-10°C~60°C
TEMPERATURE	-10 6 00 6
STORAGE	-20°C∼70°C
TEMPERATURE	
WARRANTY	1 Year