



FEATURES

- 21.5" true color LCD, resolution 1920 x 1080.
- The touch screen uses a full plane capacitive touch screen, up to 35 million clicks.
- DC in connector to meet the industrial field power supply.
- The ultra-thin design saves cabinet space and is resistant to shock and vibration.
- High-precision capacitive touch screen, with many industrial site application features, while supporting panel embedded and standard VESA installation, users can flexibly choose the installation method.

PPC-10007	
LCD DISPLAY	21.5"
CPU	Intel Core i5 -6th Gen
RAM	DDR4 2133/2400/1866MHz Memory slots, up to 32GB
MAX. RESOLUTION	1920 x 1080
STORAGE	1* SATA3.0, supporting SSD
NETWORK PORT	1* Realtek RTL8111E Gigabit network card.
AUDIO	1 x Line -in; 1 x Line-out
USB	USB 3.0x2, USB2.0X2
BRIGHTNESS	300cd/m2
EXPANSION	1* Mini-PCIe Slot, supporting WIFI/4G 1* M-SATA SSD
GRAPHICS	CPU Integrated graphics HD Graphics and support 1080p HD photo quality
CONTRAST	1000:1
DISPLAY RATIO	16:9
TYPES	10point projective capacitive
VIEW ANGLE	89°/89°/89°/89° (R/L/U/D)
RESPONSE TIME	15ms
DISPLAY PORTS	1 * VGA, 1 * HDMI
SERIAL PORTS	2 * RS232
CONSTANT TEMPERATURE	5%~95% @ 40° C
HUMIDITY TEST	Non-condensing
INSTALLATION METHOD	wall-mounting, VESA 100×100mm
POWER INPUT	Support 12V DC power supply
OVERALL DIMENSION	552mm x339mm x57mm
CERTIFICATION	CE, FCC, ROHS
OPERATING TEMPERATURE	-10℃~60℃
STORAGE TEMPERATURE	-20℃~70℃
WARRANTY	1 Year