



FEATURES

- 12.1" true colour LCD, resolution 1024 x 768.
- The touch screen uses a full plane capacitive touch screen.
- DC in connector to meet the industrial field power supply.
- The ultra-thin design saves cabinet space and is resistant to shock and vibration.
- High-precision capacitive touch screen, with many industrial site application features, while supporting panel embedded and standard VESA installation, users can flexibly choose the installation method.

PPC-10008	
LCD DISPLAY	12.1"
CPU	Intel Atom R3845, quad core, @1.91GHz,
RAM	DDR3L 1333 MHz Memory slots, up to 8GB
MAX. RESOLUTION	1024 x 768
STORAGE	1* SATA3.0, supporting SSD
NETWORK PORT	2*Intel WGI211AT 10M/100M/1000M adaptive network card, Supports network wake-up and diskless startup
AUDIO	1 x Line -in; 1 x Line-out
USB	USB 3.0x1 USB 2.0X 3
BRIGHTNESS	1000cd/m2
EXPANSION	1* Mini-PCIe Slot, supporting WIFI/4G 1* M-SATA SSD
GRAPHICS	CPU Integrated graphics HD Graphics
CONTRAST	800:1
DISPLAY RATIO	4:3
TYPES	10point projective capacitive
VIEW ANGLE	85°/85°/85°/85° (R/L/U/D)
RESPONSE TIME	<15ms
DISPLAY PORTS	1 * VGA, 1 * HDMI
SERIAL PORTS	2 * RS232
CONSTANT TEMPERATURE	5%~95% @ 40° C,
HUMIDITY TEST	Non-condensing
INSTALLATION METHOD	wall-mounting, VESA 100×100mm
POWER INPUT	Support 12V DC power supply
OVERALL DIMENSION	317mm x258mm
CERTIFICATION	CE, FCC, ROHS
OPERATING TEMPERATURE	-10℃~60℃
STORAGE TEMPERATURE	-20℃~70℃
WARRANTY	1 Year