

FEATURES

- 12.1" true colour LCD, resolution 1024 x 768.
- The touch screen uses a full plane capacitive touch screen.
- DC in connector to meet the industrial field power supply.
- The ultra-thin design saves cabinet space and is resistant to shock and vibration.
- High-precision capacitive touch screen, with many industrial site application features, while supporting panel embedded and standard VESA installation, users can flexibly choose the installation method.

PPC-10008	
LCD DISPLAY	12.1"
CPU	Intel i7-8550U 4Core and 8Thread Processor
RAM	DDR4 2133/2400 MHz Memory slots, up to 64GB
MAX.	1024 x 768
RESOLUTION	
STORAGE	1* SATA3.0, supporting SSD & M.2 slot supports 2280, SATA, NVME(PCIE) signals
NETWORK PORT	2*Realtek 8111G 10M/100M/1000M adaptive network card, Supports network
	wake-up and diskless startup
AUDIO	1 x Line -in; 1 x Line-out
USB	USB 3.0x1 USB 2.0X 3
BRIGHTNESS	350cd/m2
EXPANSION	1*Mini-PCIE interface Support WIFI/3G/4G/GPS/Bluetooth, etc
GRAPHICS	CPU Integrated graphics HD Graphics
CONTRAST	700:1
DISPLAY RATIO	4:3
TYPES	10point projective capacitive
VIEW ANGLE	80°/80°/70°/70° (R/L/U/D)
RESPONSE TIME	<8ms
DISPLAY PORTS	1 * VGA, 1 * HDMI
SERIAL PORTS	2 * RS232
CONSTANT	5%~95% @ 40° C
TEMPERATURE	
HUMIDITY TEST	Non-condensing
INSTALLATION	wall-mounting, VESA 100×100mm
METHOD	
POWER INPUT	Support 12V DC power supply
OVERALL	317mm x258mm
DIMENSION	or rec pour
CERTIFICATION	CE, FCC, ROHS
OPERATING TEMPERATURE	-10°C∼60°C
STORAGE	-20°C∼70°C
TEMPERATURE	-20 G - 70 G
WARRANTY	1 Year
VVAINIANTT	1 ICai