PPC-10009



FEATURES

- 7" true color LCD, resolution 1024x600 optional, backlight service life up to 15000 hours.
- The touch screen uses a full plane capacitive touch screen, up to
 35 million clicks.
- 12v voltage DC power input, to meet the industrial field power supply.
- The ultra-thin design saves cabinet space and is resistant to shock and vibration.
- High-precision capacitive touch screen, with many industrial site application features, while supporting panel embedded and standard VESA installation, users can flexibly choose the installation method.

PPC-10009	
LCD DISPLAY	7"
CPU	I5-6300U with 2.5Ghz two core four thread processor,15w TDP
RAM	1 x DDR4 2666(max 16gb)
MAX.	1024 x 600
RESOLUTION	
STORAGE	1 x SATA 2.5, 1X M-SATA
NETWORK PORT	2 x Intel Gigabit Ethernet
AUDIO	1 x MIC
USB	2 * USB 2.0 port, 2 * USB 3.0 port
BRIGHTNESS	300cd/m2
EXPANSION	IP65
GRAPHICS	7" TFT LED
CONTRAST	500:1
SERIAL PORT	3 x RS232
TYPES	High precision capacitive
CLICK LIFE	120 grams of strength, 35 million times
RESPONSE TIME	<8ms
TRANSMITTANCE	above 85%
HIGH	55°C/240hr
TEMPERATURE	
TEST	
CONSTANT	50 °C, 90%RH
TEMPERATURE	
HUMIDITY TEST	240 hrs
INSTALLATION	Panel embedded, with support for VESA installation
METHOD	43.86
POWER INPUT	12 DC power supply
OVERALL	196mm x 140mm x 48.2mm
DIMENSION	CL LCC
CERTIFICATION OPERATING	CE, FCC -10°C∼60°C
TEMPERATURE	-10 C~00 C
STORAGE	-20°C∼70°C
TEMPERATURE	-20 6 - 70 6
WARRANTY	1 Year
WAINIANTI	I lear