



## FEATURES

- 7" true color LCD display with 1024\*600 resolution
- Intel® Celeron® J6412, Quad-core, clock speed 2.00 GHz, up to 2.60GHz 10W
- 1024 \* 600 Resolution.
- 9~ 36v DC power input.
- High-precision capacitive screen
- standard VESA mounting are supported.
- 4 x USB, 2 x GLAN

| PPC-22001              |                                                                           |
|------------------------|---------------------------------------------------------------------------|
| SIZE                   | 7"                                                                        |
| CPU                    | Intel® Celeron® J6412, Quad-core, clock speed 2.00 GHz, up to 2.60GHz 10W |
| RAM                    | DDR4-2666/2933/3200MHz, Max. up to 32GB                                   |
| RESOLUTION             | 1024(H) * 600(V)                                                          |
| STORAGE                | 1 * SATA                                                                  |
| ETHERNET               | 2 * RJ45                                                                  |
| AUDIO                  | 1 * Line-out port                                                         |
| USB                    | 3 * USB 3.0 & 2 * USB2.0                                                  |
| SERIAL PORT            | 3 * RS232                                                                 |
| BRIGHTNESS             | 1000 Cd/m2                                                                |
| DISPLAY OUTPUT         | 2 * HDMI                                                                  |
| DISPLAY                | 7" LCD Resolution                                                         |
| CONTRAST               | 700:1                                                                     |
| MAXIMUM COLOR          | 16M                                                                       |
| TOUCH                  | High precision capacitive                                                 |
| TOUCH INTERFACE        | In-Built                                                                  |
| VIEW ANGLE             | 80°/80°/80°/80° (R/L/U/D)                                                 |
| TOUCH INTERFACE        | In-Built                                                                  |
| TEMPERATURE & HUMIDITY | 40 °C, 95%RH, 240 hrs.                                                    |
| RESPONSE TIME          | < 16ms                                                                    |
| INSTALLATION           | VESA mountable with bracket                                               |
| POWER INPUT            | 9 ~ 36V DC power supply                                                   |
| COMPLIANCE             | MIL-STD-810(Vibration & Shock) / MIL-STD-461F                             |
| CABINET                | Aluminium profile face frame Abrasive back shell                          |
| TPM                    | support TPM 2.0 onboard IC                                                |
| IP STANDARD            | NA                                                                        |
| OPERATING TEMPERATURE  | -30~70℃                                                                   |
| STORAGE TEMPERATURE    | -40~85℃                                                                   |
| WARRANTY               | 2 Years                                                                   |