



FEATURES

- 19” 350 nits TFT LED Display.
- Projected Capacitive Touch.
- Streamlined enclosure for highly efficient Heat dissipation.
- Enclosed in robust aluminium casing.
- Front IP65 for protection against water and dust.
- A true flat, edge to edge design.
- Panel Embedded, VESA Mounting with Bracket.
- 12-36V DC-input.

PPC-05003	
LCD DISPLAY	19“
CPU	Intel® 3/4/6/7/8/10/11 Corei3/i5/i7
RAM	1*DDR4 SODIMM memory slot
MAX. RESOLUTION	1280 x 1024 @60Hz resolution
STORAGE	1 * M-SATA / 1 * SATA
NETWORK PORT	1 x Intel Gigabit Ethernet
VGA	1920 * 1200
HDMI	1920 * 1200
SERIAL PORT	2 * RS232
USB	4 * USB 3.0
DISPLAY	19” TFT LED
CONTRAST	800:1
MAXIMUM COLOR	16M
TYPES	High precision capacitive
AUDIO	1*Hp-out /1*Mic-in
RESPONSE TIME	<5ms
TRANSMITTANCE	up to 95%
BRIGHTNESS	350nits
CLICK LIFE CYCLE	50 Million Times
POWER INPUT	DC version: 12 ~36V DC.
OVERALL DIMENSION	435mm*360mm*57mm
OPERATING TEMPERATURE	-20 ~ 60° C
STORAGE TEMPERATURE	-30 ~ 80° C
PANEL CABINET	IP65, Aluminium alloy Mold
CERTIFICATIONS	CE, FCC, IP65(Front)
WARRANTY	1 Year