



FEATURES

- Intel Elkhart Celeron J6412 processor
- 1 x SODIMM DDR4 memory slot, maximum support 32 GB
- 1 x 2.5-inch SATA HDD/SSD
- 1 x RJ45 Console Port
- 2 x USB 3.0 ports (USB 3.0 signal colayed with 2 x M.2 3042/3052 slots)
- 2 x GbE SFP by Intel i210-IS
- 1 x HDMI Port
- 1 x M.2 2230 supports PCIe Wi-Fi (PCIe signal colayed with Port6)
- 2 x M.2 B-Key 3042/3052
- 1 x Mini PCIe slot (supports mSATA SSD, LTE or USB Wi-Fi card).

NAD-02006	
CPU	Onboard Intel Elkhart Lake Celeron J6412 processor
Chipset	SOC
RAM	1 x 260 pin SODIMM DDR4 32GB
STORAGE	1 x 2.5-inch HDD/SSD bay, 1 x Mini PCIe (SATA/USB 2.0, supporting LTE/SSD/Wi-Fi)
LAN	2 x 2.5 GbE RJ-45 by Intel i225
Console	1 x RJ45 console port
USB	2 x USB 3.0 (USB 3.0/2.0, USB 3.0 signal colayed with 2 x M.2 3042/3052 slots)
HDMI	1 x HDMI
SIM	5 x Nano SIM slot, 4 external at the front panel to M.2 3052/3042 Key B, 1 internal to Mini PCIe.
Expansion	1 x M.2 2230 supports PCIe Wi-Fi(PCIe signal colayed with Port6, default to Port6), 2 x M.2 B-Key 3042/3052 (support 5G/LTE card); 4 x Nano SIM slots(Connected to the above 2 x M.2 B key)
Watchdog	YES
GPIO	Support 4 channel input and output GPIO
TPM	1 x TPM 2.0 header
RTC	Internal RTC
POWER	40W Power Adapter/ 90~264V@47~63Hz
Power switch	1 x Power Button, 1 x Reset Button
OPERATING TEMPRATURE	0℃~45℃
STORAGE TEMPRATURE	-20℃~70℃
Humidity	5 ~ 90% non-condensing
WARANTY	2 Years
CERTIFICATION	CE, FCC, ROHS
DIMENSION	200x44x175.7mm